



EMC TEST REPORT

Dates of Tests: September 16 – 21, 2018
 Test Report S/N: LR500121810B
 Test Site : LTA Co., Ltd.

Model No.

DC-D4233HRX

APPLICANT

IDIS CO., LTD.

Equipment Name : Network Camera
Manufacturer : IDIS CO., LTD.
Model name : DC-D4233HRX
Additional Model name : NC-D4233HRX, DC-D4233WRX, NC-D4233WRX,
 DC-D4223WRX, NC-D4223WRX
Test Device Serial No.: : Identification
Directive : Electromagnetic Compatibility Directive 2014/30/EU
Rule Part(s) : EN 55032:2015
 EN 50130-4:2011/A1:2014
 EN 61000-3-2:2014
 EN 61000-3-3:2013
Data of reissue : October 10, 2018

This test report is issued under the authority of:

The test was supervised by:

Young Kyu Shin, Technical Manager

Min gi Kang, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



NVLAP LAB CODE 200723-0

Revision	Date of issue	Test report No.	Description
0	10.10.2018	LR500121810B	Initial

TABLE OF CONTENTS

1. General information's	4
2. Information's about test item	5
3. Test Report	8
3.1 Summary of tests	8
3.2 EMISSION	9
3.2.1 Conducted emissions	9
3.2.2 Radiated Emission	15
3.2.3 Harmonic Current (AC power input port)	23
3.2.4 Voltage Variation and Flicking (AC power input port).....	25
3.3 IMMUNITY	28
3.3.1 Electrostatic Discharge	28
3.3.2 RF Electromagnetic Field	30
3.3.3 Electrical fast transients	32
3.3.4 Surge	33
3.3.5 Conducted disturbances, induced by radio-frequency fields	34
3.3.6 Mains supply voltage dips, short interruptions.....	35
3.3.7 Mains supply voltage variations	36
APPENDIX A TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS.....	37
APPENDIX B PERFORMANCE CRITERIA	41
APPENDIX C PHOTOGRAPHS	44

1. General information's

1-1 Test Performed

Company name : **LTA Co., Ltd.**
 Address : 243, Jubug-ri, Yangji-Myeon, Yongin-Si, Kyunggi-Do, Korea. 449-822
 Web site : <http://www.ltalab.com>
 E-mail : chahn@ltalab.com
 Telephone : +82-31-323-6008
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2018-09-30	ECT accredited Lab.
RRA	KOREA	KR0049	-	EMC accredited Lab.
FCC	U.S.A	649054	2019-04-13	FCC CAB
VCCI	JAPAN	C-4948,	2020-09-10	VCCI registration
		T-2416,	2020-09-10	
		R-4483(10 m),	2020-10-15	
		G-847	2018-12-13	
IC	CANADA	5799A-2	2019-03-15	IC filing
KOLAS	KOREA	NO.551	2021-08-20	KOLAS accredited Lab.

2. Information's about test item

2-1 Client/ Manufacturer

Company name : IDIS CO., LTD.
 Address : 8-10, TECHNO 3-RO, YUSEONG-GU, DAEJEON, KOREA
 Telephone / Facsimile : +82-31-723-5205 / +82-31-723-5108

Factory 1

Company name : IDIS CO., LTD.
 Address : 8-10, TECHNO 3-RO, YUSEONG-GU, DAEJEON, KOREA

2-2 Equipment Under Test (EUT)

Class : A
 Equipment Name : Network Camera
 Model name : DC-D4233HRX
 Additional Model name : NC-D4233HRX, DC-D4233WRX, NC-D4233WRX, DC-D4223WRX,
 NC-D4223WRX
 DC-D4233HRX is basic model, which was tested.
 Additional Models are identical to DC-D4233HRX except for Model Name,
 marketing purpose.
 Serial number : Identification
 Date of receipt : September 05, 2018
 EUT condition : Pre-production, not damaged
 Interface ports : DC IN, LAN, Audio IN, Audio OUT, Alarm IN, Alarm OUT
 Power rating : AC 230 V, 50 Hz (Adapter) / DC 56 V (PoE)
 Modulator : -
 Crystal/Oscillator(s) : -
 Firmware version : XXXX

2-3 Modification

-NONE

2-4 Model Specification

-NONE

2-5 Test conditions

Temp. / Humid. / Pressure : +(23 - 25) °C / (49 - 50) % R.H. / (100.1) kPa
 Tested Model : DC-D4233HRX
 Test mode : Capture mode (Adapter), Capture mode (PoE)
 Power supply : AC 230 V, 50 Hz (Adapter) / DC 56 V (PoE)

2-5 EUT

Equipment	Model No.	Serial No.	Manufacturer
Network Camera	DC-D4233HRX	N/A	IDIS CO., LTD.

2-6 Accessory / Capture mode (Adapter)

Equipment	Model No.	Serial No.	Manufacturer
Adapter	DSA-36W-12136	N/A	HANSUNG
Notebook	P56	N/A	DELL
Speaker	PS-80	N/A	DELL
JIG	N/A	N/A	IDIS CO., LTD.
Mobile Phone	SHV-E210L	R33C9026JXE	DELL

/ Capture mode (PoE)

Equipment	Model No.	Serial No.	Manufacturer
PoE	NEXT-PEG4806JT	N/A	ex-net
Notebook	P56	N/A	HANSUNG
Speaker	PS-80	N/A	INTER-M
JIG	N/A	N/A	N/A
Mobile Phone	SHV-E210L	R33C9026JXE	SAMSUNG

2-7 Cable List / Capture mode (Adapter)

From		To		Length (m)	Shielding	
Type	I/O Port	Type	I/O Port		Cable	backshell
EUT	DC IN	Adapter	-	1.2	NO	Plastic
	LAN	Notebook	LAN	4.0	NO	Plastic
	Audio IN	Mobile Phone	Speaker OUT	0.2	NO	Plastic
	Audio OUT	Speaker	INPUT	0.5	NO	Plastic
	Alarm IN	JIG	-	0.5	NO	Plastic
	Alarm OUT	JIG	-	0.5	NO	Plastic
Notebook	DC IN	Adapter	-	1.2	NO	Plastic
Speaker	AC IN	AC Power Source	3 Pin AC Line	1.2	NO	Plastic
JIG	DC IN	Adapter	-	1.2	NO	Plastic

/ Capture mode (PoE)

From		To		Length (m)	Shielding	
Type	I/O Port	Type	I/O Port		Cable	backshell
EUT	PoE	PoE	Data OUT	4.0	NO	Plastic
	Audio IN	Mobile Phone	Speaker OUT	0.2	NO	Plastic
	Audio OUT	Speaker	INPUT	0.5	NO	Plastic
	Alarm IN	JIG	-	0.5	NO	Plastic
	Alarm OUT	JIG	-	0.5	NO	Plastic
Notebook	DC IN	Adapter	-	1.2	NO	Plastic
	LAN	PoE	Data IN	2.0	NO	Plastic
PoE	AC IN	AC Power Source	3 Pin AC Line	1.2	NO	Plastic
Speaker	AC IN	AC Power Source	3 Pin AC Line	1.2	NO	Plastic
JIG	DC IN	Adapter	-	1.2	NO	Plastic

3. Test Report

3.1 Summary of tests

Parameter	Applied Standard	Status
I. Emission		
Radiated Emission	EN 55032:2015	C
Conducted Emission	EN 55032:2015	C
Harmonic Current Emission	EN 61000-3-2:2014	NA ^{Note 3}
Voltage Fluctuations and Flicker	EN 61000-3-3:2013	C
II. Immunity		
Electrostatic Discharge	EN 61000-4-2:2009	C
RF Electromagnetic field	EN 61000-4-3:2006/A1:2008/A2:2010	C
Fast Transients Common mode	EN 61000-4-4:2012	C
Surges, line to line and line to ground	EN 61000-4-5:2014/A1:2017	C
RF common mode	EN 61000-4-6:2014/AC:2015	C
Voltage dips and Interruptions	EN 61000-4-11:2004/A1:2017	C
Main supply voltage variations	EN 50130-4:2011/A1:2014	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

Note 3: We did not test EN61000-3-2 (Harmonic current emissions) for the DC-D4233HRX because equipment whose rated power is less or equal 75W don't need to be tested.

3.2 EMISSION

3.2.1 Conducted emissions

Definition:

The test assesses the ability of the EUT to limit its internal noise from being present on the AC mains Power In/Output ports.

We were performed the test according to LTA procedure LTA-QI-04.

Measurement Frequency range	: 150 kHz – 30 MHz
Test method	: EN 55032:2015
Measurement RBW	: 9 kHz
Test mode	: Capture mode (Adapter), Capture mode (PoE)
Result	: Complies

Measurement Data:

- Refer to the Next page (Maximum emission configuration)

A sample calculation:

COR. F (correction factor)= LISN Insertion loss + Cable loss + Pulse Limiter Factors

Emission Level= meter reading + COR.F

Limits for conducted disturbance at the mains ports of class A ITE

Frequency Range	Quasi-peak	Average
(0.15 – 0.5) MHz	79 dBuV	66 dBuV
(0.5 – 30) MHz	73 dBuV	60 dBuV

Note: The limits will decrease with the frequency logarithmically within 0.15MHz to 0.5MHz

Limits for conducted disturbance at the mains ports of class B ITE

Frequency Range	Quasi-peak	Average
(0.15 – 0.5) MHz	(66 – 56) dBuV	(56 - 46) dBuV
(0.5 – 5) MHz	56 dBuV	46 dBuV
(5 – 30) MHz	60 dBuV	50 dBuV

Note: The limits will decrease with the frequency logarithmically within 0.15 MHz to 0.5 MHz

Limits of conducted common mode (asymmetric mode) disturbance at telecommunication ports in the frequency range 0.15 MHz to 30 MHz for class A equipment

Frequency Range	Voltage limits		Current limits	
	Quasi-peak	Average	Quasi-peak	Average
(0.15 – 0.5) MHz	(97 – 87) dBuV	(84 – 74) dBuV	(53 – 43) dBuV	(40 – 30) dBuV
(0.5 – 30) MHz	87 dBuV	74 dBuV	43 dBuV	30 dBuV

Note 1: The limits decrease linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Note 2: The current and voltage disturbance limits are derived for use with an impedance stabilization network (ISN) which presents a common mode (asymmetric mode) impedance of 150Ω to the telecommunication port under test (conversion factor is $20 \log_{10} 150/I = 44$ dB)

Limits of conducted common mode (asymmetric mode) disturbance at telecommunication ports in the frequency range 0.15 MHz to 30 MHz for class B equipment

Frequency Range	Voltage limits		Current limits	
	Quasi-peak	Average	Quasi-peak	Average
(0.15 – 0.5) MHz	(84 – 74) dBuV	(74 – 64) dBuV	(40 – 30) dBuV	(30 – 20) dBuV
(0.5 – 30) MHz	74 dBuV	64 dBuV	30 dBuV	20 dBuV

Note 1: The limits decrease linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Note 2: The current and voltage disturbance limits are derived for use with an impedance stabilization network (ISN) which presents a common mode (asymmetric mode) impedance of 150Ω to the telecommunication port under test (conversion factor is $20 \log_{10} 150/I = 44$ dB)


Conducted emissions (LINE) / Capture mode (Adapter)



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No. : DC-D4233HRX Phase : LINE
Test Mode : Capture mode (Adapter) Test Power : 230 / 50
Temp. / Humi. : 24 / 55 Test Engineer : KANG M G

Data: 1518 File: D:\Conducted Data\2018\LTA_Conduction_2018_9.EM6 (1577)



Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV	dB	QP	AV	QP	AV	QP	AV
	dBuV	dBuV		dBuV	dBuV	dBuV	dBuV	dB	dB
0.153	23.17	7.33	19.51	42.68	26.84	79.00	66.00	36.32	39.16
0.155	22.85	7.11	19.51	42.36	26.62	79.00	66.00	36.64	39.38
0.162	21.80	6.46	19.51	41.31	25.97	79.00	66.00	37.69	40.03
12.869	8.61	3.76	19.93	28.54	23.69	73.00	60.00	44.46	36.31
26.247	0.39	-4.94	20.43	20.82	15.49	73.00	60.00	52.18	44.51
27.272	3.46	-3.03	20.41	23.87	17.38	73.00	60.00	49.13	42.62

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter


Conducted emissions (NEUTRAL) / Capture mode (Adapter)



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No. : DC-D4233HRX Phase : NEUTRAL
 Test Mode : Capture mode (Adapter) Test Power : 230 / 50
 Temp. / Humi. : 24 / 55 Test Engineer : KANG M G

Data: 1521 File: D:\Conducted Data\2018\LTA_Conduction_2018_9.EM6 (1577)



Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV	dB	QP	AV	QP	AV	QP	AV
	dBuV	dBuV		dBuV	dBuV	dBuV	dBuV	dB	dB
0.150	22.39	6.55	19.50	41.89	26.05	79.00	66.00	37.11	39.95
0.158	21.82	6.81	19.50	41.32	26.31	79.00	66.00	37.68	39.69
11.770	9.19	4.29	19.92	29.11	24.21	73.00	60.00	43.89	35.79
23.024	-3.00	-7.77	20.47	17.47	12.70	73.00	60.00	55.53	47.30
26.091	0.15	-4.90	20.53	20.68	15.63	73.00	60.00	52.32	44.37
27.113	4.10	-2.28	20.53	24.63	18.25	73.00	60.00	48.37	41.75

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conducted emissions (TEL_1000 M) / Capture mode (Adapter)




4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No. : DC-D4233HRX Phase : TEL_1000M
Test Mode : Capture mode (Adapter) Test Power : 230 / 50
Temp. / Humi. : 24 / 55 Test Engineer : KANG M G

Data: 1535 File: D:\Conducted Data\2018\LTA_Conduction_2018_9.EM6 (1577)

Date: 2018-09-21



Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV	dB	QP	AV	QP	AV	QP	AV
	dBuV	dBuV		dBuV	dBuV	dBuV	dBuV	dB	dB
4.356	28.80	20.12	19.30	48.10	39.42	87.00	74.00	38.90	34.58
4.422	29.18	20.27	19.30	48.48	39.57	87.00	74.00	38.52	34.43
4.501	30.80	24.78	19.31	50.11	44.09	87.00	74.00	36.89	29.91
4.565	28.74	20.31	19.31	48.05	39.62	87.00	74.00	38.95	34.38
4.696	30.73	25.80	19.32	50.05	45.12	87.00	74.00	36.95	28.88
25.865	24.04	23.34	19.79	43.83	43.13	87.00	74.00	43.17	30.87

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conducted emissions (TEL_1000 M) / Capture mode (PoE)




4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No. : DC-D4233HRX Phase : TEL_1000M
Test Mode : Capture mode (PoE) Test Power : 230 / 50
Temp. / Humi. : 24 / 55 Test Engineer : KANG M G

Data: 1543 File: D:\Conducted Data\2018\LTA_Conduction_2018_9.EM6 (1577)

Date: 2018-09-21



Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV	dB	QP	AV	QP	AV	QP	AV
	dBuV	dBuV		dBuV	dBuV	dBuV	dBuV	dB	dB
0.391	36.86	36.86	19.45	56.31	56.31	89.04	76.04	32.73	19.73
1.763	34.89	34.65	19.26	54.15	53.91	87.00	74.00	32.85	20.09
4.504	35.16	35.15	19.31	54.47	54.46	87.00	74.00	32.53	19.54
5.875	35.07	35.08	19.35	54.42	54.43	87.00	74.00	32.58	19.57
7.245	34.69	34.70	19.40	54.09	54.10	87.00	74.00	32.91	19.90
15.861	34.38	33.91	19.64	54.02	53.55	87.00	74.00	32.98	20.45

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

3.2.2 Radiated Emission

Definition:

The test assesses the ability of ancillary equipment to limit their internal noise from being radiated from the enclosure. We were performed the test according to LTA procedure LTA-QI-04.

Test method	: EN 55032:2015
Measuring Distance	: 10 m for below 1 GHz / 3 m for above 1 GHz
Measurement Frequency range	: 30 MHz – 6 000 MHz
Measurement RBW	: 120 kHz @ 10 m / 1 MHz @ 3 m
Test mode	: Capture mode (Adapter), Capture mode (PoE)
Result	: Complies

Measurement Data:

- Refer to the Next page (Maximum emission configuration)

- The highest internal source of an EUT is higher than 108 MHz, the measurement shall be made up to 6 GHz.
(The highest internal source of an EUT : 1 GHz)

A sample calculation:

COR. F (correction factor)= Antenna factor + Cable loss- Amp.gain- Distance correction

Emission Level= meter reading + COR.F

Limit of 10 m for below 1 GHz

CLASS A

Frequency Range	Quasi-peak
(30 – 230) MHz	40 dBuV/m
(230 – 1 000) MHz	47 dBuV/m

CLASS B

Frequency Range	Quasi-peak
(30 – 230) MHz	30 dBuV/m
(230 – 1 000) MHz	37 dBuV/m

Limit of 3m for above 1 GHz

CLASS A

Frequency Range	Average Limit @ 3m (dB μ V/m)	Peak limit @ 3m (dB μ V/m)
(1 000 – 3 000) MHz	56	76
(3 000 – 6 000) MHz	60	80
NOTE:	The lower limit applies at the transition frequency.	

CLASS B

Frequency Range	Average Limit @ 3m (dB μ V/m)	Peak limit @ 3m (dB μ V/m)
(1 000 – 3 000) MHz	50	70
(3 000 – 6 000) MHz	54	74
NOTE:	The lower limit applies at the transition frequency.	

Radiated Emission (Below 1 GHz) / V _ Capture mode (Adapter)




4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: DC-D4233HRX Temp/Humi: 25 / 53

Test Mode : Capture mode (Adapter) Tested by: KANG M G

Data: 915 File: C:\Program Files (x86)\e3\1809-1.EM6 (1142)



Freq MHz	Reading dBuV	C.F dB	Result QP dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
259.88	58.69	-16.01	42.68	47.00	4.32	100	240	VERTICAL
400.00	51.36	-12.44	38.92	47.00	8.08	101	319	VERTICAL
500.00	52.17	-10.60	41.57	47.00	5.43	101	255	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emission (Below 1 GHz) / H _ Capture mode (Adapter)




4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: DC-D4233HRX Temp/Humi: 25 / 53

Test Mode : Capture mode (Adapter) Tested by: KANG M G

Data: 914 File: C:\Program Files (x86)\e3\1809-1.EM6 (1142)



Freq MHz	Reading dBuV	C.F dB	Result QP dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
259.87	59.49	-16.01	43.48	47.00	3.52	318	252	HORIZONTAL
297.01	50.11	-14.62	35.49	47.00	11.51	271	357	HORIZONTAL
600.02	45.83	-7.97	37.86	47.00	9.14	277	44	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emission (Below 1 GHz) / V _ Capture mode (PoE)




4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: DC-D4233HRX Temp/Humi: 25 / 53

Test Mode : Capture mode (PoE) Tested by: KANG M G

Data: 930 File: C:\Program Files (x86)\e3\1809-1.EM6 (1142)



Freq MHz	Reading dBuV	C.F dB	Result QP dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
50.44	52.05	-17.61	34.44	40.00	5.56	102	180	VERTICAL
259.87	56.19	-16.01	40.18	47.00	6.82	294	122	VERTICAL
594.00	50.50	-8.18	42.32	47.00	4.68	110	359	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emission (Below 1 GHz) / H _ Capture mode (PoE)




4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: DC-D4233HRX Temp/Humi: 25 / 53

Test Mode : Capture mode (PoE) Tested by: KANG M G

Data: 929 File: C:\Program Files (x86)\e3\1809-1.EM6 (1142)




Freq MHz	Reading dBuV	C.F dB	Result QP dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
259.87	56.09	-16.01	40.08	47.00	6.92	339	47	HORIZONTAL
499.99	46.00	-10.60	35.40	47.00	11.60	166	225	HORIZONTAL
599.99	47.24	-7.97	39.27	47.00	7.73	168	263	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emission (Above 1 GHz) _ Capture mode (Adapter)


EUT/Model No.: DC-D4233HRX Temp/Humi: 25 / 53

 Test Mode : Capture mode (Adapter) Tested by: KANG M G



EUT/Model No.: DC-D4233HRX Temp/Humi: 25 / 53

 Test Mode : Capture mode (Adapter) Tested by: KANG M G




Manufacture : IDIS CO., LTD. Test Date 2018-09-17 Temp.: 25 Humidity : 53 Distance (m) 3.8
 Model : DC-D4233HRX
 TEST mode : Capture mode (Adapter)
 Ver Data: 948 Hor Data: 947

Freq.(MHz)	Reading(PK)	Reading(AV)	C.F	Result(PK)	Result(AV)	Limit(PK)	Limit(AV)	Margin(PK)	Margin(AV)	Height	Angle	Polarity
MHz	dBuV	dBuV	dB	dBuV/m	dBuV/m	dBuV/m	dBuV/m	dB	dB	cm	deg	Hor/Ver
1780.0	50.5	41.9	-3.04	47.47	38.87	76.0	56.0	28.53	17.13	100	349	H
5310.0	41.9	24.8	12.93	54.84	37.72	80.0	60.0	25.16	22.28	100	203	H
5635.0	34.4	24.3	13.91	48.30	38.21	80.0	60.0	31.70	21.79	100	344	H
1780.0	51.5	41.0	-3.04	48.47	37.97	76.0	56.0	27.53	18.03	100	319	V
2000.0	47.4	29.7	0.07	47.49	29.74	76.0	56.0	28.51	26.26	100	332	V
2595.0	45.6	30.0	2.53	48.12	32.52	76.0	56.0	27.88	23.48	100	125	V

Radiated Emission (Above 1 GHz) _ Capture mode (PoE)


EUT/Model No.: DC-D4233HRX Temp/Humi: 25 / 53

 Test Mode : Capture mode (PoE) Tested by: KANG M G



EUT/Model No.: DC-D4233HRX Temp/Humi: 25 / 53

 Test Mode : Capture mode (PoE) Tested by: KANG M G



Manufacture : IDIS CO., LTD. Test Date 2018-09-17 Temp.: 25 °C Humidity : 53 % Distance (m) 3.8
 Model : DC-D4322HRX
 TEST mode : Capture mode (PoE)
 Ver Data: 938 Hor Data: 937

Freq. (MHz)	Reading(PK)	Reading(AV)	C.F	Result(PK)	Result(AV)	Limit(PK)	Limit(AV)	Margin(PK)	Margin(AV)	Height	Angle	Polarity
MHz	dBuV	dBuV	dB	dBuV/m	dBuV/m	dBuV/m	dBuV/m	dB	dB	cm	deg	Hor/Ver
5005.0	34.6	24.1	12.66	47.22	36.80	80.0	60.0	32.78	23.20	100	318	H
5125.0	35.5	24.6	12.47	47.94	37.11	80.0	60.0	32.06	22.89	100	102	H
5260.0	35.3	24.4	12.71	48.04	37.14	80.0	60.0	31.96	22.86	100	125	H
1780.0	51.9	38.5	-3.04	48.85	35.47	76.0	56.0	27.15	20.53	100	127	V
2000.0	47.6	32.3	0.07	47.70	32.34	76.0	56.0	28.30	23.66	100	144	V
2590.0	46.0	29.9	2.5	48.49	32.40	76.0	56.0	27.51	23.60	100	119	V

3.2.3 Harmonic Current (AC power input port)

Definition:

This part deals with the Limitation of harmonic currents injected into the public supply system.



We were performed the test according to LTA procedure LTA-QI-04.

Test method	:	EN 61000-3-2:2014
Test mode	:	Capture mode (Adapter)
Rated power	:	3.540 W
Result	:	Not Applicable

Measurement Data:

- We did not test EN61000-3-2 (Harmonic current emissions) for the DC-D4233HRX because equipment whose rated power is less or equal 75W don't need to be tested.

Harmonic Current (AC power input port) / Capture mode (Adapter)

21st September 2018 - 15:16:49		Page 1/1	IECSoft v2_5a
		IEC61000-3-2:2014 Fluctuating Harmonics	
			
Instrument Details			
Instrument Model	PPA5511		
Serial Number	162-04957		
Firmware Version	2.168		
N4L Calibration Date	18th September 2017		
Instrument Version	Standard		
Test Settings			
Class	Class A		
Mode	Measured		
Equipment Under Test			
Brand	IDIS CO., LTD.		
Model	DC-D4233HRX		
Serial	N/A		
Impedance Network ID	N/A		
Test Conditions			
	User Entered	Measured	
Rated Voltage	N/A	230.935V	
Rated Current	N/A	50.825mA	
Rated Frequency	N/A	50.000Hz	
Rated Power	N/A	3.540W	
Additional Test Information			
Measured Power Factor	0.302		
Max Current THD	187.39%		
Max THC	51.804mA		
Max Power	3.584W		
Max F.Current	29.070mA		
Average F.Current	28.090mA		
Minimum Current	100A		
Test Duration	2.5 minutes		
Additional Test Details			
Operator	N/A		
Lab Name	N/A		
Location	N/A		
Notes			
Signature			
Results	Test - N/A. Rated Power < 75W		

Test not applicable

With the exception of lighting equipment section 7 of the IEC61000-3-2:2014 standard declares that no Harmonic current limits are specified for equipment with a rated power of

3.2.4 Voltage Variation and Flicking (AC power input port)

Definition:

This section is concerned with the limitation of voltage fluctuations and flicker impressed on the public low-voltage system.


We were performed the test according to LTA procedure LTA-QI-04.

Test method	:	EN 61000-3-3:2013
Test mode	:	Capture mode (Adapter)
Result	:	Complies

Measurement Data:

- Refer to the Next page

Voltage Variation and Flicking (AC power input port) / Capture mode (Adapter)

21st September 2018 - 14:55:15		Page 1/2	IECSoft v2_5a
		IEC61000-3-3:2013 Ed.3.0 Flickermeter	
Instrument Details			
Instrument Model	PPA5511		
Serial Number	162-04957		
Firmware Version	2.168		
N4L Calibration Date	18th September 2017		
Instrument Version	Standard		
Test Settings			
Class	Voltage		
Mode	Normal (4%)		
Minimum Current	10A		
PST	10.00 minutes		
PLT	12 PSTs		
Equipment Under Test			
Brand	IDIS CO., LTD.		
Model	DC-D4233HRX		
Serial	N/A		
Impedance Network ID	N/A		
Test Conditions			
	User Entered	Measured	
Rated Voltage	N/A	230.934V	
Rated Current	N/A	N/A	
Rated Frequency	N/A	50.000Hz	
Rated Power	N/A	N/A	
D max	0.0690% (Limit: 4.0%)		
T max	0.0000 s (Limit: 0.5 s)		
DC max	0.0078% (Limit: 3.3%)		
Additional Test Details			
Operator	N/A		
Lab Name	N/A		
Location	N/A		
Notes			
Signature			
Results	Phase1: PASS		

21st September 2018 - 14:55:15		Ph:1 Page 2/2		IECSoft v2_5a				
IEC61000-3-3:2013 Ed.3.0 Flickermeter								
Instrument Details								
Instrument Model	PPA5511							
Instrument Serial	162-04957							
Instrument Firmware	2.168							
Equipment Under Test								
Brand	IDIS CO., LTD.							
Model	DC-D4233HRX							
Serial	N/A							
Flicker Test Results								
PST no.	Status	DC (%)	Dmax (%)	Tmax (s)	PST	PST Lim	PLT	PLT Lim
1	Phase1: PASS	0.008	0.06896	0	0.082	1.00	N/A	N/A

3.3 IMMUNITY

3.3.1 Electrostatic Discharge

Definition:

The test assesses the ability of the EUT to operate as intended in the event of an electrostatic discharge.

We were performed the test according to LTA procedure LTA-QI-04.

Test date	:	2019.09.18.
Test method	:	EN 61000-4-2 :2009
Temperature / Humidity / Pressure	:	23 °C / 46 % R.H. / 100 kPa
Discharge Impedance	:	(330 ±10%)Ω / (150 ±10%) pF
Type of Discharge (air discharge)	:	± 2kV, ± 4 kV, ± 8 kV
Type of Discharge (contact discharge)	:	± 6 kV
Number of discharges at each point	:	10 of each polarity
Discharge Repetition on Rate	:	1 / sec
Test mode	:	Capture mode (Adapter), Capture mode (PoE)
Result	:	Complies

Measurement Data:

- Refer to the Next page

1-1. Indirect Discharge

No.	Position	Kind of Discharge	Results	Remarks
1	HCP	Contact	Complies	No reaction recognized
2	VCP	Contact	Complies	No reaction recognized


1-2. Direct Discharge

No.	Position	Kind of Discharge	Result	Remarks
1	Enclosure #1	Contact	Complies	No reaction recognized
2	Enclosure #2	Air	Complies	No reaction recognized
3	Screw	Air	Complies	No reaction recognized

※ Results are complies in each test mode.

ESD TEST POINT

- ← Air discharge
- ← Contact discharge



3.3.2 RF Electromagnetic Field

Definition:

The test assesses the ability of the EUT to operate as intended in the presence of a radio frequency electromagnetic field disturbance.

We were performed the test according to LTA procedure LTA-QI-04.

Test date	:	2018.09.16.
Test method	:	EN 61000-4-3:2006/A1:2008/A2:2010
Temperature / Humidity / Pressure	:	22 °C / 44 % R.H. / 99 kPa
Frequency range	:	80 MHz to 2,700 MHz
Test level	:	10 V/m (measured unmodulated)
Amplitude Modulation	:	AM, 80 %, 1 kHz Sinusoidal PM, 1 Hz (0.5s ON : 0.5s OFF)
Step size	:	1 % of fundamental
Dwell Time	:	3 s
Test mode	:	Capture mode (Adapter), Capture mode (PoE)
Result	:	Complies

Measurement Data:

MODE : Capture mode (Adapter)

Port	Side	Result	Remarks
Horizontal	Front	Complies	No reaction recognized
	Left	Complies	No reaction recognized
	Rear	Complies	No reaction recognized
	Right	Complies	No reaction recognized
Vertical	Front	Complies	No reaction recognized
	Left	Complies	No reaction recognized
	Rear	Complies	No reaction recognized
	Right	Complies	No reaction recognized

Audio Port	Result	Remarks
AUDIO OUT	Complies	No reaction recognized

MODE : Capture mode (PoE)

Port	Side	Result	Remarks
Horizontal	Front	Complies	No reaction recognized
	Left	Complies	No reaction recognized
	Rear	Complies	No reaction recognized
	Right	Complies	No reaction recognized
Vertical	Front	Complies	No reaction recognized
	Left	Complies	No reaction recognized
	Rear	Complies	No reaction recognized
	Right	Complies	No reaction recognized

Audio Port	Result	Remarks
AUDIO OUT	Complies	No reaction recognized

※ Results are complies in each test mode.

3.3.3 Electrical fast transients

Definition:

The test assesses the ability of the EUT to operate as intended in the event of fast transients presence on one of the input/output ports.

We were performed the test according to LTA procedure LTA-QI-04.

Test date	:	2018.09.18.
Test method	:	EN 61000-4-4:2012
Temperature / Humidity / Pressure	:	23 °C / 46 % R.H. / 100 kPa
Cable length	:	> 3 m
Test level	:	2.0 kV (AC power input port) 1.0 kV (Signal port)
Polarity	:	Negative/ positive
Repetition frequency	:	100 kHz
Test mode	:	Capture mode (Adapter), Capture mode (PoE)
Result	:	Complies

Measurement Data:

MODE : Capture mode (Adapter)

AC power Line	Test level	Result	Remarks
L – N - PE	± 2 kV	Complies	No reaction recognized

Signal Line	Test level	Result	Remarks
LAN	± 1 kV	Complies	No reaction recognized

MODE : Capture mode (PoE)

Signal Line	Test level	Result	Remarks
PoE	± 1 kV	Complies	No reaction recognized

※ Results are complies in each test mode.

3.3.4 Surge

Definition:

The test assesses the ability of the EUT to operate as intended in the event of surge presence on the AC main power input ports.

We were performed the test according to LTA procedure LTA-QI-04.

Test date	:	2018.09.18.
Test method	:	EN 61000-4-5:2014/A1:2017
Temperature / Humidity / Pressure	:	24 °C / 46 % R.H. / 100 kPa
Test level	:	± 0.5 kV, ±1 kV (line to line) ± 0.5 kV, ± 1 kV, ± 2 kV (line to ground), ± 0.5 kV, ± 1 kV (signal line)
Polarity	:	Negative/ positive
Wave shape	:	1.2/ 50 μs pulse
Number of surges	:	5 (at each phase)
Test mode	:	Capture mode (Adapter), Capture mode (PoE)
Result	:	Complies

Measurement Data:

MODE : Capture mode (Adapter)

Phase	Line	level	Result	Remark
0°	Line(L) to line(N)	± 0.5, 1.0 kV	Complies	No reaction recognized
90°	Line(L) to line(N)	± 0.5, 1.0 kV	Complies	No reaction recognized
180°	Line(L) to line(N)	± 0.5, 1.0 kV	Complies	No reaction recognized
270°	Line(N) to ground(PE)	± 0.5, 1.0 kV	Complies	No reaction recognized

Signal Line	level	Result	Remark
LAN	± 0.5, 1.0 kV	Complies	No reaction recognized

MODE : Capture mode (PoE)

Signal Line	level	Result	Remark
PoE	± 0.5, 1.0 kV	Complies	No reaction recognized

※ Results are complies in each test mode.

3.3.5 Conducted disturbances, induced by radio-frequency fields

Definition:

The test assesses the ability of the EUT to operate as intended in the presence of a radio frequency electromagnetic disturbance on the input/output ports.

We were performed the test according to LTA procedure LTA-QI-04.

Test date	:	2018.09.16.
Test method	:	EN 61000-4-6:2014/AC:2015
Temperature / Humidity / Pressure	:	23 °C / 44 % R.H. / 99 kPa
Frequency range	:	0.15MHz – 100 MHz
Test level	:	10 Vrms unmodulated
Amplitude Modulation	:	AM, 80 %, 1 kHz Sinusoidal PM, 1 Hz (0.5s ON : 0.5s OFF)
Step size	:	1 % of fundamental.
Test mode	:	Capture mode (Adapter), Capture mode (PoE)
Result	:	Complies

Measurement Data:

MODE : Capture mode (Adapter)

Port	Test level (Vrms)	Result	Remarks
Power Line	10	Complies	No reaction recognized

Signal Port	Test level (Vrms)	Result	Remarks
LAN	10	Complies	No reaction recognized

Audio Port	Test level (Vrms)	Result	Remarks
AUDIO OUT	10	Complies	No reaction recognized

MODE : Capture mode (PoE)

Port	Test level (Vrms)	Result	Remarks
PoE	10	Complies	No reaction recognized

Audio Port	Test level (Vrms)	Result	Remarks
AUDIO OUT	10	Complies	No reaction recognized

※ Results are complies in each test mode.

3.3.6 Mains supply voltage dips, short interruptions

Definition:

The test assesses the ability of the EUT to operate as intended in the event of voltage dips and interruptions present on the AC mains power input ports.

We were performed the test according to LTA procedure LTA-QI-04.

Test date	:	2018.09.18.
Test method	:	EN 61000-4-11:2004/A1:2017
Temperature / Humidity / Pressure	:	23 °C / 46 % R.H. / 100.1 kPa
Ut	:	230 Vac
Test mode	:	Capture mode (Adapter)
Result	:	Complies

Measurement Data:

MODE : Capture mode (Adapter)

Test Level %Ut	Voltage droop and interruptions %Ut	Duration of Reduction (period)	Result	Remarks
80	20	250	Complies	No reaction recognized
70	30	25	Complies	No reaction recognized
40	60	10	Complies	No reaction recognized
0	100	250	Complies	EUT OFF during the test. Re-operated without user's control. After the test, EUT was operated normally.

3.3.7 Mains supply voltage variations

Definition:

The test assesses the ability of the EUT to operate as intended in the event of voltage variations present on the AC mains power input ports.

We were performed the test according to LTA procedure LTA-QI-04.

Test date	:	2018.09.18.
Test method	:	EN 50130-4:2011/A1:2014
Temperature / Humidity / Pressure	:	23 °C / 46 % R.H. / 100.1 kPa
Supply Voltage maximum	:	$U_{nom} + 10 \%$
Supply Voltage minimum	:	$U_{nom} - 15 \%$
Ut	:	230 Vac
Test mode	:	Capture mode (Adapter)
Result	:	Complies

Measurement Data:

U_{nom} = Nominal mains voltage. Where provision is made to adapt the equipment to suit a number of nominal supply voltages (e.g. by transformer tap changing), the above conditioning severity shall be applied for each nominal voltage, with the equipment suitably adapted. For equipment which is claimed to be suitable for a range of nominal mains voltages (e.g. 220/240 V) without adaptation, $U_{max} = (\text{Maximum } U_{nom}) + 10 \%$, and $U_{min} = (\text{Minimum } U_{nom}) - 15 \%$. In any case the range of U_{nom} must include the European nominal mains voltage of 230 V.

2 Mains supply voltage variations

MODE : Capture mode (Adapter) / 230 V, 50 Hz

Test LevelCondition		Test Level (V)	Result	Remarks
Unom	+10%	253	Complies	No reaction recognized
Unom	-15%	195.5	Complies	No reaction recognized

APPENDIX A

TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment are identified by the Test Laboratory.

Conducted emissions

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
<input checked="" type="checkbox"/>	EMI TEST Receiver	ESR	Rohde & Schwarz	101499	2019.07.11	1 year
<input checked="" type="checkbox"/>	Pulse Limiter	ESH3-Z2	Rohde & Schwarz	100710	2019.03.19	1 year
<input type="checkbox"/>	LISN	ESH3-Z6	Rohde & Schwarz	100378	2019.09.07	1 year
<input type="checkbox"/>	LISN	ESH3-Z6	Rohde & Schwarz	101468	2019.09.07	1 year
<input checked="" type="checkbox"/>	LISN	ENV216	Rohde & Schwarz	101222	2019.09.07	1 year
<input checked="" type="checkbox"/>	LISN	LT32C/10	AFJ	32031518210	2019.09.06	1 year
<input checked="" type="checkbox"/>	TEST PROGRAM	e3_Ver: 5.5.201a	AUDIX	-	-	-
<input type="checkbox"/>	ISN	ISN T800	TESEQ	27109	2019.09.12	1 year
<input checked="" type="checkbox"/>	ISN	ENY81-CA6	Rohde & Schwarz	101565	2019.09.12	1 year
<input type="checkbox"/>	CURRENT PROBE	EZ-17	Rohde & Schwarz	100508	2019.09.06	1 year

Radiated Emission – Below 1 GHz

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
<input checked="" type="checkbox"/>	EMI TEST Receiver	ESCI7	Rohde & Schwarz	100772	2019.09.06	1 year
<input checked="" type="checkbox"/>	Amplifier (25 dB)	8447D	HP	2944A07684	2019.09.06	1 year
<input checked="" type="checkbox"/>	TRILOG Antenna	VULB9160	SCHWARZBECK	9160-3237	2019.05.16 (KOLAS)	2 year
<input checked="" type="checkbox"/>	TEST PROGRAM	e3_Ver: 6.2009-10-12a	AUDIX	-	-	-

Radiated Emission – Above 1 GHz

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
<input checked="" type="checkbox"/>	EMI TEST Receiver	ESCI7	Rohde & Schwarz	100772	2019.09.06	1 year
<input checked="" type="checkbox"/>	Amplifier	8449B	HP	3008A00671	2019.09.06	1 year
<input checked="" type="checkbox"/>	HORN ANTENNA	3115	ETS	114105	2019.11.03 (KOLAS)	2 year
<input checked="" type="checkbox"/>	TEST PROGRAM	e3_Ver: 6.2009-10-12a	AUDIX	-	-	-

Harmonic Current / Voltage Variation and Flicking

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
<input checked="" type="checkbox"/>	Precision Power Analyzer	PPA551	Newtons4th Ltd	162-04957	2018.09.18	1 year
<input checked="" type="checkbox"/>	Reference Impedance Network	ES4152	NF Corp.	9074424	2018.09.07	1 year

Electrostatic Discharge

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
<input checked="" type="checkbox"/>	ESD Simulator	ESS-2000	NOISEKEN	ESS0625187	2019.03.20	1 year
<input checked="" type="checkbox"/>	ESD GUN	TC-815P	NOISEKEN	ESS0382069	2019.03.20	

RF Electromagnetic Field

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
<input checked="" type="checkbox"/>	Signal Generator	E4432B	Agilent	MY41310632	2019.05.15	1 year
<input checked="" type="checkbox"/>	Power Meter	E4419B	Agilent	GB38410133	2019.05.15	1 year
<input checked="" type="checkbox"/>	Power Sensor	E9300A	Agilent	MY41497992	2019.05.15	1 year
<input checked="" type="checkbox"/>	Power Sensor	E9300A	Agilent	MY41497618	2019.05.15	1 year
<input checked="" type="checkbox"/>	RF POWER AMPLIFIER	ITA0300KL-300	INFINITECH	0300KL 1507 001	-	-
<input checked="" type="checkbox"/>	RF POWER AMPLIFIER	ITA2000KL-120	INFINITECH	200KL 1507 001	-	-
<input checked="" type="checkbox"/>	RF POWER AMPLIFIER	ITA4500KL-70	INFINITECH	4500KL 1507 001	-	-
<input checked="" type="checkbox"/>	RF POWER AMPLIFIER	ITA0750KL-300	INFINITECH	0750KL 1507 001	-	-
<input checked="" type="checkbox"/>	Log.-Per.Antenna (80 MHz ~ 3 GHz)	K9128	RAPA	NONE	-	-
<input checked="" type="checkbox"/>	Signal Generator	SMB 100A	R&S	177621	2019.03.19	1 year
<input checked="" type="checkbox"/>	HORN ANTENNA	3115	ETS	00055005	-	-
<input checked="" type="checkbox"/>	Sound Acoustic Tester	TST-1000	TESTEK	150065-A	2019.09.11	1 year

Electrical fast transients

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
<input checked="" type="checkbox"/>	Compact Generator	NX5	EMTEST	P1640185038	2019.03.19	1 year
<input checked="" type="checkbox"/>	AC Power Source	Variac NX1-260-16	EMTEST	P1648188071	2019.03.19	1 year
<input checked="" type="checkbox"/>	Capacitive Coupling Clamp	CCI	EMTEST	P1703190739	2019.03.19	1 year

Surge

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
<input checked="" type="checkbox"/>	Compact Generator	NX5	EMTEST	P1640185038	2019.03.19	1 year
<input checked="" type="checkbox"/>	AC Power Source	Variac NX1-260-16	EMTEST	P1648188071	2019.03.19	1 year
<input checked="" type="checkbox"/>	CDN	CNV508N1	EMTEST	P1623180335	2019.03.19	1 year

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
<input checked="" type="checkbox"/>	Compact Generator	Compact NX	EMTEST	P1725200196	2019.09.06	1 year
<input checked="" type="checkbox"/>	AC Power Source	Variac NX	EMTEST	P1745207276	2019.09.06	1 year
<input checked="" type="checkbox"/>	CDN	CNV 508T5	EMTEST	P1742204978	2019.09.07	1 year
<input checked="" type="checkbox"/>	CDN	CNV 508N1	EMTEST	P1742204940	2019.09.07	1 year

Conducted disturbances, induced by radio-frequency fields

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
<input checked="" type="checkbox"/>	Signal generator	SML03	R&S	103026/0013	2019.03.19	1 year
<input checked="" type="checkbox"/>	Power Meter	NRVD	R&S	101689	2019.03.19	1 year
<input checked="" type="checkbox"/>	Power Sensor	URV5-Z2	R&S	100755	2019.03.19	1 year
<input checked="" type="checkbox"/>	Power Sensor	URV5-Z2	R&S	100756	2019.03.19	1 year
<input checked="" type="checkbox"/>	RF Power Amplifier	FLL75A	FRANKONIA	1033	-	-
<input checked="" type="checkbox"/>	EM INJECTION CLAMP	TSIC-23	F.C.C	529	2019.05.16	1 year
<input type="checkbox"/>	CDN (M1)	TSCDN-M1-16A	F.C.C	07004	2019.09.06	1 year
<input checked="" type="checkbox"/>	CDN (M2)	TSCDN-M2-16A	F.C.C	07008	2019.09.06	1 year
<input checked="" type="checkbox"/>	CDN (M3)	TSCDN-M3-16A	F.C.C	07017	2019.09.06	1 year
<input checked="" type="checkbox"/>	Sound Acoustic Tester	TST-1000	TESTEK	15065-A	2019.09.11	1 year

Mains supply voltage dips, short interruptions

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
<input checked="" type="checkbox"/>	Compact Generator	NX5	EMTEST	P1640185038	2019.03.19	1 year
<input checked="" type="checkbox"/>	AC Power Source	Variac NX1-260-16	EMTEST	P1648188071	2019.03.19	1 year

Mains supply voltage variations

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
<input checked="" type="checkbox"/>	Compact Generator	NX5	EMTEST	P1640185038	2019.03.19	1 year
<input checked="" type="checkbox"/>	AC Power Source	Variac NX1-260-16	EMTEST	P1648188071	2019.03.19	1 year

APPENDIX B
PERFORMANCE CRITERIA

Performance criteria

The variety and the diversity of the apparatus within the scope of this document makes it difficult to define precise criteria for the evaluation of the immunity test results.

If as a result of the application of the tests defined in this standard, the apparatus becomes dangerous or unsafe then the apparatus shall be deemed to have failed the test.

A functional description and a definition of performance by the manufacture and noted in the test report, based on the following criteria:

Electrostatic discharge

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change. The EUT shall meet the acceptance criteria for the functional test (see Clause 6), after the conditioning.

Radiated electromagnetic fields

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the conditioning is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change, and no such flickering of indicators occurs at a field strength of 3 V/m.

For components of CCTV systems, where the status is monitored by observing the TV picture, then deterioration of the picture is allowed at 10 V/m, providing.

(a) there is no permanent damage or change to the EUT

(e.g. no corruption of memory or changes to programmable setting etc.)

(b) at 3 V/m, any deterioration of the picture is so minor that the system could still be used; and

(c) there is no observable deterioration of the picture at 1 V/m.

The EUT shall meet the acceptance criteria for the functional test(see Clause 6), after the conditioning.

Fast transient burst / slow high energy voltage surge

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of the bursts is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change. The EUT shall meet the acceptance criteria for the functional test (see Clause 6), after the conditioning.

Slow high energy voltage surge

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of the surges is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change. The EUT shall meet the acceptance criteria for the functional test (see Clause 6), after the conditioning.

Conducted RF immunity

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the conditioning is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change, and no such flickering of indicators occurs at $U_0 = 130 \text{ dB}\mu\text{V}$.

For components of CCTV systems, where the status is monitored by observing the TV picture, then deterioration of the picture is allowed at $U_0 = 140 \text{ dB}\mu\text{V}$, providing

- (a) there is no permanent damage or change to the EUT
(e.g. no corruption of memory or changes to programmable settings, etc.)
- (b) at $U_0 = 130 \text{ dB}\mu\text{V}$, any deterioration of the picture is so minor that the system could still be used, and
- (c) there is no observable deterioration of the picture at $U_0 = 120 \text{ dB}\mu\text{V}$.

The EUT shall meet the acceptance criteria for the functional test(see Clause 6), after the conditioning.

Voltage dip/interruption

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the conditioning is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change. The EUT shall meet the acceptance criteria for the functional test(see Clause 6), after the conditioning.

It is permitted to use ancillary equipment (e.g. A UPS) to meet the requirements of this clause. This shall be detailed in the test report and the manufacturer's installation manual.

Signaling a mains fault during the 100 % voltage reduction test is permitted.

Mains supply voltage variations

There shall be no damage, malfunction or change of status due to the different supply voltage conditions. The EUT shall meet the acceptance criteria for the functional test(see Clause 6), during the conditioning.

APPENDIX C
PHOTOGRAPHS

Conducted emission (Maximum emission configuration) / Capture mode (Adapter)




Conducted emission (Maximum emission configuration) _ TEL / Capture mode (Adapter)





Conducted emission (Maximum emission configuration) _ TEL / Capture mode (PoE)





Radiated emission (Maximum emission configuration)-Below 1 GHz / Capture mode (Adapter)





Radiated emission (Maximum emission configuration)-Below 1 GHz / Capture mode (PoE)



Radiated emission (Maximum emission configuration) – Above 1GHz / Capture mode (Adapter)



Radiated emission (Maximum emission configuration) – Above 1GHz / Capture mode (PoE)



Harmonic Current / Voltage Variation and Flicking / Capture mode (Adapter)




Electrostatic discharge / Capture mode (Adapter)



Electrostatic discharge / Capture mode (PoE)





RF Electromagnetic Field / Capture mode (Adapter)




RF Electromagnetic Field / Capture mode (PoE)




Electrical fast transients / Capture mode (Adapter)



Electrical fast transients / Capture mode (PoE)




Surge / Capture mode (Adapter)




Surge / Capture mode (PoE)




Conducted Disturbances, Induced by Radio-Frequency Fields / Capture mode (Adapter)



Conducted Disturbances, Induced by Radio-Frequency Fields / Capture mode (PoE)



Main supply voltage dips, short interruptions / Capture mode (Adapter)



EUT



EUT

